

Door Motion Technologies[®], Inc.

DuraSwing[™] Series Door Operators



DS MK IV

DS MK V

DS 4R

DS 4H

DS 4S

DS 4C

DESCRIPTION	APPLICATION	COLORS	ITEMS INCLUDED
Commercial. On demand, open only.	Store front glass, aluminum hollow metal or wood swing door. Uses existing hydraulic closer.	Mill finish (silver) Duranodic (dark bronze) Taupe	Wireless receiver. Offset 27" actuator arm. Mounting hardware.
Commercial. Full-time. Power open/hydraulic close.	Store front glass, aluminum hollow metal or wood swing door. Has internal hydraulic closer.	Mill finish (silver) Duranodic (dark bronze)	Wireless receiver. Straight actuator arm. Mounting hardware.
Residential Power-open, power-close	Automates all interior/exterior residential doors. Trigger to open, trigger to close.	Mill finish (silver) Duranodic (dark bronze) Taupe	Straight actuator arm. 16" track. Wireless receiver. Mounting hardware.
Elevator - (Swing type hatch door)	Hatch door mounted. Requires one for each level. Trigger to open, auto-close.	Mill finish (silver) Duranodic (dark bronze) Taupe	Straight actuator arm. 16" track. Mounting hardware.
Elevator - (Slide gate)	Cab mounted. Safety gate: accordion, scissors, two-speed, tambor. Trigger to close, trigger to open.	Mill finish (silver) Duranodic (dark bronze) Taupe	Re-handable offset actuator arm. 9" slide track. Mounting hardware.
Elevator Swing-type hatch door.	Cab mounted. Will open all in-line hatch doors. Requires spring hinge for each door. Trigger to open, auto close.	Mill finish (silver) Duranodic (dark bronze) Taupe	Straight actuator arm. Mounting hardware.

NOTES:

- Red designates elevator & lift application
- MK 4R - Generally requires an electric strike. Control & 24V DC provided by door operator. (All DS series have this feature).
- MK 4C - Requires at least one adjustable spring hinge to be mounted on each hatch door.
- All operations may be controlled with wireless transmitters (see accessories sheet).
- As needed, actuator arms and (or) tracks may be interchanged.